




## HYDRAFORCE CARTRIDGE QUICK REFERENCE

### Poppet, 2-Way, Normally Closed with Reverse Flow Energized





SL08-22 / SV08-22 / SF08-22 / SV10-22  
SV12-22 / SV16-22 / HSV10-22 / SF20-22

SV10-(P)22(A) / SV12-(P)22(A)




Cartridge Size	Flow	Option (* Select Option)	Line Body			
SL08-22*-6T-N-***/**	1.5 lpm / 0.4 gpm	None = Blank	6T	Alum.	7024660	9/16" UNF
SV08-22*-6T-N-***/**	26 lpm / 7 gpm	Y = MANUAL O/RIDE	6T	Alum.	7024660	9/16" UNF
SF08-22*-6TD-P-***/**	23 lpm / 6 gpm	J = MANUAL O/RIDE	6TD	Duct. Iron	7151010	9/16" UNF
HSV10-22*-8HT-U-***/**	76 lpm / 20 gpm	S = 150u Screen	8HT	Duct. Iron	7158110	3/4" UNF
SV10-(P)22(A)*-8T-N-***/**	57 lpm / 15 gpm	M = MANUAL O/RIDE	8T	Alum.	7024280	3/4" UNF
SV12-(P)22(A)*-10T-N-***/**	114 lpm / 30 gpm		10T	Alum.	7022240	7/8" UNF
HSV12-22*-16HT-U-***/**	114 lpm / 30 gpm		16HT	Duct. Iron	7158420	1-5/16" UNF
SV16-22*-12T-N-***/**	132 lpm / 35 gpm		12T	Alum.	7023230	1-1/16" UNF
SF20-22*-20TD-P-***/**	303 lpm / 80 gpm		20TD	Duct. Iron	4553870	1-5/8" UNF
Seals	Voltage (Standard Coils)*	Voltage (E Coils)***	Termination (Standard V)	Termination (Standard A)	Termination (Standard E Coils)**	
N = Buna N	12 = 12VDC	12 = 12VDC	DS = Dual Spade	AG = Din (6316115/63162)	ER = Deutsch DT04-2P (IP69K) (4303612/4303624)	
N = Buna N	24 = 24VDC	24 = 24VDC	DG = Din (6306012/6306024)		EY = Metric-Pack 150 (IP69K)	
P = Polyurethane	115 = 115VAC		DL = Leadwires			
U = Urethane	230 = 230VAC		DL/W = Leadwires/weatherpak			
N = Buna N			DR = Deutsch DT04-2P			
N = Buna N						
U = Urethane						
N = Buna N						
P = Polyurethane						

### Poppet, 2-Way, Normally Open with Reverse Flow De-energized



SV08-23 / SF08-23 / SV10-23  
SV12-23 / SV16-23 / HSV10-23 / SF20-23

SV10-(P)23(A) / SV12-(P)23(A)



Cartridge Size	Flow	Option (* Select Option)	Line Body			
SV08-23*-6T-N-***/**	30 lpm / 8 gpm	None = Blank	6T	Alum.	7024660	9/16" UNF
SF08-23*-6T-P-***/**	30 lpm / 8 gpm	P = MANUAL O/RIDE NO K	6T	Alum.	7024660	9/16" UNF
SV10-(P)23(A)*-8T-N-***/**	68 lpm / 18 gpm	K = MANUAL O/RIDE KNO	8T	Alum.	7024280	3/4" UNF
HSV10-23*-8HT-U-***/**	76 lpm / 20 gpm	HP = MANUAL O/RIDE WH	8HT	Duct. Iron	7158110	3/4" UNF
SV12-(P)23(A)*-10T-N-***/**	114 lpm / 30 gpm	S = 150u Screen	10T	Alum.	7022240	7/8" UNF
SV16-23*-12T-N-***/**	132 lpm / 35 gpm		12T	Alum.	7023230	1-1/16" UNF
SF20-23*-20TD-P-***/**	303 lpm / 80 gpm		20TD	Duct. Iron	4553870	1-5/8" UNF
Seals	Voltage (Standard Coils)*	Voltage (E Coils)***	Termination (Standard V)	Termination (Standard A)	Termination (Standard E Coils)**	
N = Buna N	12 = 12VDC	12 = 12VDC	DS = Dual Spade	AG = Din (6316115/63162)	ER = Deutsch DT04-2P (IP69K) (4303612/4303624)	
P = Polyurethane	24 = 24VDC	24 = 24VDC	DG = Din (6306012/6306024)		EY = Metric-Pack 150 (IP69K)	
N = Buna N	115 = 115VAC		DL = Leadwires			
U = Urethane	230 = 230VAC		DL/W = Leadwires/weatherpak			
N = Buna N			DR = Deutsch DT04-2P			
N = Buna N						
P = Polyurethane						