





## HYDRAFORCE CARTRIDGE QUICK REFERENCE

### Spool, 6-Way, 2-Position



Cartridge Size	Flow	Option (* Select Option)	Line Body			
SV12-60*-8T-***/**	45 lpm / 12 gpm	P = MANUAL O/RIDE PUSH T = MAN O/RIDE 3 POSITION DETENT K = MANUAL O/RIDE KNOB	8T	Alum.	7021470	3/4" UNF
Seals	Voltage (Standard Coils)*	Voltage (E Coils)***	Termination (Standard V)	Termination (Standard AC)	Termination (Standard E Coils)**	
N = Buna N	12 = 12VDC 24 = 24VDC 115 = 115VAC	12 = 12VDC 24 = 24VDC	DS = Dual Spade DG = Din (6306012/6306024) DL = Leadwires	AG = Din (6316115/63162)	ER = Deutsch DT04-2P (IP69K) (4303612/4303624) EY = Metric-Pack 150 (IP69K)	
	24 = 24VDC 115 = 115VAC	24 = 24VDC	DG = Din (6306012/6306024) DL = Leadwires		EY = Metric-Pack 150 (IP69K)	

### Spool, 6-Way, 2-Position for Selector or Series/Parallel Drive Circuits



Cartridge Size	Flow	Option (* Select Option)	Line Body			
SV80-61	7.6 lpm / 2 gpm		6T	Alum.	4553010	9/16" UNF
Seals	Voltage (Standard Coils)*	Voltage (E Coils)***	Termination (Standard V)	Termination (Standard AC)	Termination (Standard E Coils)**	
N = Buna N	12 = 12VDC 24 = 24VDC 115 = 115VAC	12 = 12VDC 24 = 24VDC	DS = Dual Spade DG = Din (6306012/6306024) DL = Leadwires	AG = Din (6316115/63162)	ER = Deutsch DT04-2P (IP69K) (4303612/4303624) EY = Metric-Pack 150 (IP69K)	
	24 = 24VDC 115 = 115VAC	24 = 24VDC	DG = Din (6306012/6306024) DL = Leadwires		EY = Metric-Pack 150 (IP69K)	