



## HYDRAFORCE CARTRIDGE QUICK REFERENCE

### Proportional Directional Control, 5-Way, 3-Position, for Load Sense Applications





SP10-57C

SP08-57D 7 SP10-57D



Cartridge Size	Flow	Option (* Select Option)	Line Body			
SP10-57C*-8T-N-***/**	23 lpm / 6 gpm	M = MANUAL O/RIDE	8T	Alum.	7022830	3/4" UNF
SP08-57D*-6T-N-***/**	9.5 lpm / 2.5 gpm		6T	Alum.	7022820	9/16" UNF
SP10-57D*-8T-N-***/**	23 lpm / 6 gpm		8T	Alum.	7022830	3/4" UNF
<b>Seals</b>	<b>Voltage (Standard Coils)*</b>	<b>Voltage (E Coils)***</b>	<b>Termination (Standard V)</b>	<b>Termination (Standard AC)</b>	<b>Termination (Standard E Coils)**</b>	
N = Buna N	12 = 12VDC	12 = 12VDC	DS = Dual Spade	AG = Din (6316115/63162)	ER = Deutsch DT04-2P (IP69K) (4303612/4303624)	
	24 = 24VDC	24 = 24VDC	DG = Din (6306012/6306024)		EY = Metric-Pack 150 (IP69K)	
	115 = 115VAC		DL = Leadwires			
	24 = 24VDC	24 = 24VDC	DG = Din (6306012/6306024)		EY = Metric-Pack 150 (IP69K)	
	115 = 115VAC		DL = Leadwires			

### Proportional Directional Control, 5-Way, 3-Position, Brake Release Applications



Cartridge Size	Flow	Option (* Select Option)	Line Body			
SP10-58C*-8T-N-***/**	23 lpm / 6 gpm	M = MANUAL O/RIDE	8T	Alum.	7022830	3/4" UNF
<b>Seals</b>	<b>Voltage (Standard Coils)*</b>	<b>Voltage (E Coils)***</b>	<b>Termination (Standard V)</b>	<b>Termination (Standard AC)</b>	<b>Termination (Standard E Coils)**</b>	
N = Buna N	12 = 12VDC	12 = 12VDC	DS = Dual Spade	AG = Din (6316115/63162)	ER = Deutsch DT04-2P (IP69K) (4303612/4303624)	
	24 = 24VDC	24 = 24VDC	DG = Din (6306012/6306024)		EY = Metric-Pack 150 (IP69K)	
	115 = 115VAC		DL = Leadwires			
	24 = 24VDC	24 = 24VDC	DG = Din (6306012/6306024)		EY = Metric-Pack 150 (IP69K)	
	115 = 115VAC		DL = Leadwires			

### Proportional Directional Control, 5-Way, 3-Position, with Brake Release Port



Cartridge Size	Flow	Option (* Select Option)	Line Body			
SP08-58D*-6T-N-***/**	9.5 lpm / 2.5 gpm	M = MANUAL O/RIDE	6T	Alum.	7022820	9/16" UNF
SP10-58D*-8T-N-***/**	23 lpm / 6 gpm		8T	Alum.	7022830	3/4" UNF
<b>Seals</b>	<b>Voltage (Standard Coils)*</b>	<b>Voltage (E Coils)***</b>	<b>Termination (Standard V)</b>	<b>Termination (Standard AC)</b>	<b>Termination (Standard E Coils)**</b>	
N = Buna N	12 = 12VDC	12 = 12VDC	DS = Dual Spade	AG = Din (6316115/63162)	ER = Deutsch DT04-2P (IP69K) (4303612/4303624)	
	24 = 24VDC	24 = 24VDC	DG = Din (6306012/6306024)		EY = Metric-Pack 150 (IP69K)	
	115 = 115VAC		DL = Leadwires			
	24 = 24VDC	24 = 24VDC	DG = Din (6306012/6306024)		EY = Metric-Pack 150 (IP69K)	
	115 = 115VAC		DL = Leadwires			