HYDRAFORCE CARTRIDGE QUICK REFERENCE

Spool, 3-Way









SV07-31 / SV08-31



SV38-31J



SV07-34 / SV10-34 / SV12-34

SV10-31 / SV12-31



SV08-30 / SV38-30 / SV58-30





SV08-33 / SV10-33 / SV12-33

Cartridge Size	*Flow*	*Option (* Select Option)*	*Line Body*			
SV08-30*-6T-N-***/**	15 lpm / 4 gpm	Y = MANUAL O/RIDE	6T	Alum.	7024760	9/16" UNF
SV38-30*-6T-N-***/**	18 lpm / 5 gpm	J = MANUAL O/RIDE THRE	6T	Alum.	7024760	9/16" UNF
SV58-30*-6TD-N-***/**	15 lpm / 4 gpm	M = MANUAL O/RIDE	6TD	Duct. Iron	7151110	9/16" UNF
SV07-31*-6T-N-***/**	6 lpm / 1.6 gpm	P = MANUAL O/RIDE NO KNOB				
SV08-31*-6T-N-***/**	11 lpm / 3 gpm	K = MANUAL O/RIDE KNOB	6T	Alum.	7024760	9/16" UNF
SV38-31J-6T-N-***/**	11 lpm / 3 gpm		6T	Alum.	7024760	9/16" UNF
SV10-31*-8T-N-***/**	22 lpm / 6 gpm		8T	Alum.	7024380	3/4" UNF
SV12-31*-10T-N-***/**	60 lpm / 16 gpm		10T	Alum.	7022330	7/8" UNF
SV08-33*-6T-N-***/**	11 lpm / 3 gpm		6T	Alum.	7024760	9/16" UNF
SV10-33*-8T-N-***/**	19 lpm / 5 gpm		8T	Alum.	7024380	3/4" UNF
SV12-33*-10T-N-***/**	60 lpm / 16 gpm		10T	Alum.	7022330	7/8" UNF
SV07-34 (SPECIAL)	13 lpm / 3.5 gpm					
SV10-34*-8T-N-***/**	23 lpm / 6 gpm		8T	Alum.	7024380	3/4" UNF
SV12-34*-10T-N-***/**	60 lpm / 16 gpm		10T	Alum.	7022330	7/8" UNF
SV07-35 (SPECIAL)	11 lpm / 3 gpm					
SV08-35*-6T-N-***/**	11 lpm / 3 gpm		6T	Alum.	7024760	9/16" UNF
Seals	***Voltage (Standard Coils)****	***Voltage (E Coils)*****	***Termination (Standard VD***	***Termination (Standard AC***	***Termination (Standard E Coils)*****	
N = Buna N	12 = 12VDC	12 = 12VDC	DS = Dual Spade	AG = Din ***(6316115/63162***	ER = Deutsch DT04-2P (IP69K) ***(4303612/4303624)***	
N = Buna N	24 = 24VDC	24 = 24VDC	DG = Din ***(6306012/6306024)***		EY = Metric-Pack 150 (IP69K)	
P = Polyurethane	115 = 115VAC		DL = Leadwires			
N = Buna N	230 = 230VAC		DL/W = Leadwires/weatherpak			
N = Buna N			DR = Deutsch DT04-2P			
N = Buna N						
N = Buna N						
N = Buna N						
N = Buna N						
N = Buna N						
N = Buna N						
N = Buna N						
N = Buna N						
N = Buna N						
N = Buna N						

Spool, 3-Way, 2-Position





Cartridge Size	*Flow*	*Option (* Select Option)*	*Line Body*			
SV38-38*-6T-N-***/**	11 lpm / 3 gpm	P = MANUAL O/RIDE NO K	6T	Alum.	7024760	9/16" UNF
		K = MANUAL O/RIDE KNOB				
Seals	***Voltage (Standard Coils)****	***Voltage (E Coils)*****	***Termination (Standard VD***	***Termination (Standard AC***	***Termination (Standard E Coils)*****	
N = Buna N	12 = 12VDC	12 = 12VDC	DS = Dual Spade	AG = Din ***(6316115/63162***	ER = Deutsch DT04-2P (IP69K) ***(4303612/4303624)***	
	24 = 24VDC	24 = 24VDC	DG = Din ***(6306012/6306024)***		EY = Metric-Pack 150 (IP69K)	
	115 = 115VAC		DL = Leadwires			
	230 = 230VAC		DL/W = Leadwires/weatherpak			
			DR = Deutsch DT04-2P			